

TOWN OF LEE, BOARD OF HEALTH

GE-Pittsfield/Housatonic River Site  
Rest of River (GECD850)

Pre-Design Investigation Work Plan for Upland Disposal Facility

SATURDAY NOVEMBER 19, 2022

EXHIBIT-5



**Andrew T. Silfer**

Leader, Pittsfield/Housatonic River

General Electric Company  
Global Operations – Environment, Health & Safety  
1 Plastics Avenue  
Pittsfield, MA 01201  
T 518-937-7257 and 413-553-6602  
andrew.silfer@ge.com

*Via Electronic Mail*

November 24, 2021

Mr. Dean Tagliaferro  
EPA Project Coordinator  
U.S. Environmental Protection Agency  
c/o HDR, Inc.  
10 Lyman Street, Suite 2  
Pittsfield, MA 01201

**Re: GE-Pittsfield/Housatonic River Site  
Rest of River (GECD850)  
Pre-Design Investigation Work Plan for Upland Disposal Facility**

Dear Mr. Tagliaferro:

In accordance with the approved Final Revised Rest of River Statement of Work, enclosed for EPA's review and approval is GE's Pre-Design Investigation Work Plan for the Upland Disposal Facility.

Please let me know if you have any questions about this Work Plan.

Very truly yours,

*Andrew T. Silfer*/CSC

Andrew T. Silfer, P.E.  
GE Project Coordinator

Enclosure

Cc: (via electronic mail)

Richard Fisher, EPA  
Tim Conway, EPA  
John Kilborn, EPA  
Christopher Ferry, ASRC Primus  
Thomas Czelusniak, HDR Inc.  
Scott Campbell, Taconic Ridge Environmental  
Izabella Zapisek, Taconic Ridge Environmental  
Michael Gorski, MassDEP  
Elizabeth Stinehart, MassDEP  
John Ziegler, MassDEP  
Ben Guidi, MassDEP  
Michelle Craddock, MassDEP  
Jeffrey Mickelson, MassDEP  
Mark Tisa, MassDFW  
Jonathan Regosin, MassDFW  
Betsy Harper, MA AG  
Traci Iott, CT DEEP  
Susan Peterson, CT DEEP  
Graham Stevens, CT DEEP  
Lori DiBella, CT AG  
Molly Sperduto, USFWS  
Field Supervisor, USFWS  
Mark Barash, US DOI  
Ken Finkelstein, NOAA  
James McGrath, City of Pittsfield  
Michael Coakley, PEDAC  
Melissa Provencher, BRPC  
Christopher Ketchen, Town of Lenox  
Town Administrator, Lee  
Town Manager, Great Barrington  
Town Administrator, Stockbridge  
Town Administrator, Sheffield  
Andrew Thomas, GE  
Kevin Mooney, GE  
Matthew Calacone, GE  
Mark Gravelding and Phil Batten, Arcadis  
Dennis Lowry, AECOM  
James Bieke, Sidley Austin  
Michael Werth, Anchor QEA  
Public Information Repository at David M. Hunt Library in Falls Village, CT  
GE Internal Repository

General Electric Company

# **Pre-Design Investigation Work Plan for Upland Disposal Facility**

November 2021

# Pre-Design Investigation Work Plan for Upland Disposal Facility

November 2021

**Prepared By:**

Arcadis U.S., Inc.  
One Lincoln Center, 110 West Fayette Street, Suite 300  
Syracuse, New York 13202  
Phone: 315 446 9120  
Fax: 315 449 0017

And

AECOM  
500 Enterprise Drive  
Rocky Hill, Connecticut 06067  
Phone: 860 263 5810

**Prepared For:**

General Electric Company  
1 Plastics Avenue  
Pittsfield, Massachusetts 01201

**Our Ref:**

30103563

## Contents

<b>1</b>	<b>Introduction .....</b>	<b>1</b>
1.1	Background .....	1
1.2	Purpose and Objectives .....	2
1.3	PDI Work Plan Organization .....	2
<b>2</b>	<b>Performance Standards for UDF .....</b>	<b>3</b>
<b>3</b>	<b>Site Background and Historical Site Data Summary .....</b>	<b>5</b>
3.1	Site Description .....	5
3.2	Existing Site Information .....	5
3.2.1	Topography .....	5
3.2.2	Habitat .....	5
3.2.3	Cultural Resources Assessment .....	6
3.2.4	Utilities .....	7
3.2.5	Soils .....	7
3.2.6	Groundwater Elevations .....	7
3.2.7	Groundwater Quality .....	8
<b>4</b>	<b>Preliminary Conceptual UDF Design Summary .....</b>	<b>9</b>
4.1	Site Layout .....	9
4.2	Anticipated UDF Design .....	9
<b>5</b>	<b>Pre-Design Investigation .....</b>	<b>10</b>
5.1	Data Collection Objectives .....	10
5.2	Site Data Collection .....	10
5.2.1	Baseline Habitat Assessment .....	10
5.2.2	Topographic Field Survey .....	11
5.2.3	Soil Geotechnical Investigation .....	12
5.2.3.1	Soil Boring Program .....	12
5.2.3.2	Soil Testing for Engineering Properties .....	13
5.2.4	Soil Quality Testing .....	14
5.2.5	Piezometer and Groundwater Well Installation .....	15
5.2.5.1	Temporary Piezometer Well Installation .....	15
5.2.5.2	Permanent Monitoring Well Installation at UDF Perimeter .....	15

5.2.6	Groundwater Depth Monitoring.....	16
5.2.7	Groundwater Testing for Environmental Quality .....	16
5.2.8	Phase 1A Cultural Resources Assessment .....	16
5.3	Sampling and Analysis Procedures .....	18
5.4	Health and Safety.....	19
6	Data Evaluation and PDI Reporting .....	20
6.1	Data Evaluation .....	20
6.2	Reporting.....	20
7	Schedule.....	22
8	References .....	23

## Tables

Table 1 – Proposed Soil Boring Details

Table 2 – Proposed Temporary Piezometer Construction Details

Table 3 – Proposed Monitoring Well Construction Details

## Figures

Figure 1 – Site Plan

Figure 2 – Proposed Field Survey Activities

Figure 3 – Proposed Soil Geotechnical Investigation

Figure 4 – Proposed Soil Quality Investigation

Figure 5 – Proposed Groundwater Depth Investigation

Figure 6 – Proposed Groundwater Quality Investigation

## Appendices

Appendix A. UDF/GE Parcel Habitat Inventory Form

Appendix B. USACE Wetland Determination Data Form for the Northeast Region

Appendix C. Arcadis Field Guide for USCS Soil Classification

## Abbreviations

amsl	above mean sea level
APE	Area of Potential Effects
Arcadis	Arcadis US, Inc.
ASTM	ASTM International
bgs	below ground surface
CD	Consent Decree for GE-Pittsfield/Housatonic River Site
cm/s	centimeter per second
CRA	Cultural Resource Assessment
EPA	US Environmental Protection Agency
Eversource	Eversource Energy
Final Revised SOW	Final Revised Rest of River Statement of Work (September 2021)
FSP/QAPP	Field Sampling Plan/Quality Assurance Project Plan
ft	feet
GE	General Electric Company
IPaC	Information for Planning and Consultation (USFWS)
Lane	The Lane Construction Corporation
MACRIS	Massachusetts Cultural Resource Information System
MassDEP	Massachusetts Department of Environmental Protection
MHC	Massachusetts Historical Commission
mil	one thousandth (0.001) of an inch
MNHESP	Massachusetts Natural Heritage Endangered Species Program
NGVD 29	National Geodetic Vertical Datum of 1929
NRHP	National Register of Historic Places
OLIVER	MassGIS On-line Data Viewer application
PCB	polychlorinated biphenyl
PDI	pre-design investigation
PDI Work Plan	Pre-Design Investigation Work Plan



## Pre-Design Investigation Work Plan

Revised Permit	Final Revised Modification of GE's Resource Conservation and Recovery Act Corrective Action Permit (December 2020)
ROR	Rest of River
SPT	standard penetration test
SRHP	State Register of Historic Places
UDF	Upland Disposal Facility
USFWS	U.S. Fish and Wildlife Service
VOCs	volatile organic compounds

# 1 Introduction

This Pre-Design Investigation Work Plan (PDI Work Plan) has been prepared on behalf of the General Electric Company (GE) to present the proposed pre-design investigation (PDI) activities for the Upland Disposal Facility (UDF) and UDF support area associated with the Rest of River (ROR) Remedial Action. This section provides an overview of the site background and describes the purpose, objectives, and organization of this PDI Work Plan.

The UDF will be constructed on a 75-acre property that was formerly part of an active sand and gravel quarry and that GE acquired from The Lane Construction Corporation (Lane) in April 2021. Figure 1 shows the extent of the property acquired by GE (referred to herein as the GE Parcel). That figure also shows the maximum limits of consolidated material for the UDF and the associated operational area surrounding and encompassing the limits of the consolidated material (jointly referred to herein as the UDF area). Finally, the figure shows the potential UDF support area, which is currently undefined but may include temporary facilities such as sediment dewatering and material handling areas (referred to herein as UDF support area).

## 1.1 Background

On December 16, 2020, pursuant to the 2000 Consent Decree (CD) for the GE-Pittsfield/Housatonic River Site, the U.S. Environmental Protection Agency (EPA) issued a final revised modification of GE's Resource Conservation and Recovery Act (RCRA) Corrective Action Permit (Revised Permit) specifying a Remedial Action for the ROR area (EPA 2020). The ROR area consists of the portion of the Housatonic River and its backwaters and floodplain (excluding portions of certain residential properties) downstream of the confluence of the East and West Branches of the Housatonic River (the Confluence), which is located approximately two miles downstream from GE's former manufacturing facility in Pittsfield, Massachusetts. The selected ROR Remedial Action includes a provision for GE to construct and utilize a UDF at the former Lane site for the disposal of certain of the sediments and soils to be removed as part of the Remedial Action.

In accordance with the requirements of the Revised Permit, GE submitted to EPA a Rest of River Statement of Work (SOW) specifying the deliverables and activities that GE will conduct to design and implement the ROR Remedial Action. After receipt of EPA comments, GE submitted a Final Revised Rest of River SOW on September 14, 2021 (Anchor QEA et al. 2021).<sup>1</sup> That SOW included pre-design and design requirements for the UDF and UDF support area, including a requirement for GE to submit a PDI Work Plan for the UDF. On September 16, 2021, EPA issued an approval letter for the Final Revised SOW.

This PDI Work Plan has been prepared in accordance with the Final Revised SOW and includes descriptions for conducting desktop, field, and laboratory-based activities necessary to acquire information for design of the UDF component of the ROR Remedial Action.

---

<sup>1</sup> Although the Revised Permit is currently being appealed by other parties to the EPA Environmental Appeals Board, GE agreed in a February 10, 2020, Settlement Agreement to submit the SOW and, subject to approval by EPA, to perform the investigation and design work specified in the SOW as contractual obligations under that agreement, unless and until EPA issues a further revised permit that is not substantially similar to the current Revised Permit.

## 1.2 Purpose and Objectives

This PDI Work Plan describes the proposed investigations necessary to support engineering evaluations and detailed planning and design of the UDF. The results of activities and investigations conducted previously, as well as those performed as part of the PDI, will be used to develop the design for the construction, operation, monitoring, and maintenance of the UDF and associated facilities and for the final cover and closure of the UDF. If the findings or results of the UDF PDI activities indicate that additional investigations are necessary to facilitate the design for the UDF and/or UDF support area, a supplemental PDI work plan or an addendum to this PDI Work Plan will be submitted to EPA for review and approval prior to implementing such supplemental investigations. Further, given that the UDF support area requirements and related facilities are not known at this time, any additional investigations deemed necessary based on design requirements for the UDF support area components will be proposed and conducted within the UDF support area as part of the design process, as will be outlined in the Conceptual Design Plan for the UDF.

## 1.3 PDI Work Plan Organization

The remainder of this PDI Work Plan is organized into the following six sections:

- Section 2 presents a summary of the Performance Standards for the UDF, as described in Section II.B.5.a of the Revised Permit.
- Section 3 presents a description of the GE Parcel, including the UDF area and UDF support area, and pertinent site background and historical site data, including a summary of information currently available to support design activities.
- Section 4 presents a summary of the anticipated UDF design and site layout.
- Section 5 presents the PDI program objectives and a description of proposed desktop, field, and laboratory-based activities and investigations to address current data needs for design of the UDF and UDF support area (incorporating existing data determined to be of sufficient quality to be usable), including the following:
  - Baseline assessment of the habitat at the UDF area and UDF support area;
  - Survey of existing site features and topography;
  - Subsurface drilling for geotechnical data and sample acquisition;
  - Installation of temporary piezometers and permanent monitoring wells for baseline groundwater elevation and chemical groundwater quality monitoring; and
  - Initial Phase IA cultural resource assessment (CRA) of the UDF area and UDF support area.
- Section 6 presents a summary of data and information that will be obtained during field-based activities and the evaluations to be performed based on the acquired PDI data and information, along with a description of PDI reporting requirements.
- Section 7 presents the anticipated schedule for performing the PDI activities.

## 2 Performance Standards for UDF

Section II.B.5.a of the Revised Permit sets forth the Performance Standards for the UDF. In summary, those Performance Standards require that the UDF meet the following construction and design requirements:

- Be constructed at the location shown in Figure 6 of the Revised Permit (also depicted on Figure 1 herein).
- Provide a maximum design waste capacity of 1.3 million cubic yards.
- Have a consolidation area (defined as the waste-containing portion of the UDF) with a maximum footprint of 20 acres and a maximum elevation of 1,099 feet (ft) above mean sea level (amsl). If the seasonally high groundwater elevation is determined to be higher than 950 ft amsl, the maximum elevation of the consolidation area may be increased by the number of feet between the seasonally high groundwater and 950 ft amsl in order to achieve the maximum waste capacity of 1.3 million cubic yards.
- Include a double bottom liner, separated by a drainage layer, and incorporate primary and secondary leachate collection systems.
- Have the bottom liner a minimum of 15 ft above a conservative estimate of the seasonally high groundwater elevation. The seasonally high groundwater elevation will be projected using site-specific groundwater elevation data collected in the location of the UDF and modified to account for historical groundwater level fluctuations at similarly sited off-site long-term monitoring wells in Massachusetts. This estimation will be performed pursuant to a methodology reviewed and approved by EPA.
- Cover the consolidation area with a low-permeability cap to include liners, drainage layers, and vegetation.
- Ensure that the liners for both the bottom of the UDF and the cap have a permeability equal to or less than  $1 \times 10^{-7}$  centimeter per second (cm/s) and a minimum thickness of 30 thousands of an inch (mil) and are chemically compatible with polychlorinated biphenyls (PCBs).
- Include a stormwater management system to control surface runoff and minimize the potential for surface erosion or stormwater contribution to leachate generation.
- Include a groundwater monitoring network around the UDF to monitor for PCBs and other constituents identified in the groundwater monitoring plan as approved or modified by EPA.

Section II.B.5.a of the Revised Permit provides further that:

- GE must identify any current non-community and private water supply wells within 500 feet of the UDF consolidation area. If any such wells are identified, GE must pay the installation costs for those users to be connected to a public water supply (unless they do not consent); and if such a well owner consents at a later date or any new water users are identified within 500 feet of the UDF consolidation area, GE must pay the installation cost of a connection to a public water supply.
- GE will utilize the UDF for disposal only of sediments and soils that were generated as part of the ROR Remedial Action, and only of those sediments and soils that meet certain acceptance criteria specified in Attachment E to the Revised Permit.

## Pre-Design Investigation Work Plan

- GE will be responsible for the proper functioning of the UDF during operations, for closure of the UDF (including installation of the low-permeability cap with a vegetative cover) when the UDF is full or the ROR excavation and dredging activities have been completed, and for proper operation, maintenance, and monitoring of the closed UDF thereafter.
- No material from the ROR Remedial Action may be disposed of at any other location in Berkshire County, and no material from any portion of the GE-Pittsfield/Housatonic River Site other than the ROR or from other response actions under the CD may be disposed of at the UDF.

## 3 Site Background and Historical Site Data Summary

This section presents background information on the UDF site, including a summary of existing site information.

### 3.1 Site Description

As previously noted, Figure 1 shows the extent of the GE Parcel, the anticipated limits of consolidated material for the UDF, the UDF operational area, and the UDF support area. The GE Parcel generally consists of previously disturbed and barren ground areas void of vegetation, open grassed and wooded areas, and man-made ponds which are associated with the prior quarry operations. Additionally, there is an existing Eversource Energy (Eversource) utility easement containing overhead electric lines on the western side of the GE Parcel. The bordering site features are Valley Street to the north, Woodland Road to the east, the Lee Municipal Landfill to the south, and the remaining former Lane property (now Northeast Paving, a Division of Eurovia Atlantic Coast, LLC) to the west, which is located on Golden Hill Road.

### 3.2 Existing Site Information

Presented in the following subsections is a summary of existing information pertaining to the GE Parcel, including the UDF area and UDF support area. This information has been used in identifying the need for additional data collection, as described in this PDI Work Plan, and in developing the preliminary conceptual UDF design described herein. That information together with the supplemental information collected during implementation of this PDI Work Plan will be used in the detailed design for the UDF and associated areas.

#### 3.2.1 Topography

Topography of the entire former Lane property, including the GE Parcel, was surveyed by SK Design Group, Inc. and presented on a drawing dated June 4, 2010.<sup>2</sup> Existing topography across the GE Parcel is variable and features several localized high and low points (including pond areas) likely attributable to the site's history as a sand and gravel operation. Drainage generally pitches internally towards the localized low points. There are limited areas of the GE Parcel that drain off site to the east along Woodland Road and to the former Lane property to the west. Based on available flood insurance rate maps, the GE Parcel lays entirely outside of the mapped 500-year floodplain for the Housatonic River to the north and west (Federal Emergency Management Administration [FEMA] 1982a) and Washington Mountain Brook to the south (FEMA 1982b).

#### 3.2.2 Habitat

Preliminary information on habitat characteristics of the GE Parcel, including natural community types, the potential presence of federally listed threatened or endangered species and state-listed rare species, potential wetlands and vernal pools, and invasive species, is available from a number of existing sources. These include on-line sources, such as the MassGIS On-line Data Viewer (OLIVER), the U.S. Fish and Wildlife Service

---

<sup>2</sup> As discussed in Section 5.2.2, the topography of the GE Parcel will be re-surveyed as part of PDI activities.

(USFWS) National Wetlands Inventory (NWI) Mapping, and the Information for Planning and Consultation (IPaC), as well as aerial photograph reviews. This existing information indicates the following:

The general habitat of the GE Parcel ranges from denuded and excavated areas lacking discernible habitat (comprising the majority of the UDF area) to open areas dominated by grass and forbs to forested areas in differing stages of succession (in the northern part of the GE Parcel).

On-line mapping tools that gauge the potential habitat of areas within Massachusetts can be found through the MassGIS OLIVER. The OLIVER interactive map, available data layers, and active data layers specific to potential and documented habitats reveal that the GE Parcel does not contain any Massachusetts Natural Heritage Endangered Species Program (MNHESP) Estimated Habitats of rare wildlife or Priority Habitats of rare species, nor does it contain any MNHESP-certified or other identified vernal pools. While several habitats were identified in the surrounding geography within five miles of the GE Parcel, the nearest Priority Habitat of rare species was located 0.15 mile to the north and the nearest MNHESP-certified vernal pool was located over one mile to the southeast.

A review of the USFWS IPaC on-line mapping tool (USFWS 2021) for the GE Parcel revealed potential habitat for northern long-eared bat (a threatened species) and monarch butterfly (a candidate for listing) in the general area. Several migratory birds were also identified within the general site area, including the bald eagle, bobolink, Canada warbler, prairie warbler, and wood thrush. Given the disturbed nature of the UDF area, the forgoing species would not be expected to inhabit that specific area.

A potential wetland area has been identified on the GE Parcel consisting of an isolated palustrine, scrub/shrub, broad-leaved deciduous, seasonally flooded area off of Woodland Road (which will not be affected by the consolidation area).<sup>3</sup> In addition, the parcel contains a number of man-made or modified permanently flooded areas, which are associated with the prior quarry operations.

Overall, the data gathered from reviews of readily available on-line databases, aerial photographs, and mapping indicate that the former quarry area possesses a paucity of habitat that would be considered ecologically significant to supporting plant and animal species diversity within the immediate and surrounding geography. The northern portion of the GE Parcel supports an area of natural forested cover type which will be further investigated as described in Section 5 of this PDI Work Plan.

### 3.2.3 Cultural Resources Assessment

Existing databases have been reviewed to determine whether any cultural resources have been previously identified within the GE Parcel.<sup>4</sup> Based on review of the National Register of Historic Places (NRHP), the Massachusetts State Register of Historic Places (SRHP), and the Massachusetts Cultural Resources Information System (MACRIS), no cultural resources listed in those sources are present within the GE Parcel.

---

<sup>3</sup> As discussed in Section 5.2.1, this area will be evaluated further during PDI activities to determine whether it in fact constitutes a wetland.

<sup>4</sup> In 2008, GE submitted to EPA a report on an *Initial Phase IA Cultural Resources Assessment (CRA) for the Housatonic Rest of River Project* (URS 2008). That Initial Phase IA CRA was conducted to assess the potential for archaeological and historical resources to exist in the portions of the Housatonic River and its floodplain that could potentially be affected by implementation of remediation activities selected by EPA – namely, Reaches 5 through 8. That Initial Phase 1 CRA did not address the Lane property that is currently the GE Parcel.

### 3.2.4 Utilities

There are no known underground utilities within the GE Parcel. There is an existing overhead electric utility line and associated easement that are owned and operated by Eversource on the western edge of the site. Additional underground site utility locations are unknown at this time but are not anticipated within the limits of the UDF area and UDF support area. Dig Safe was called in fall 2019 for a groundwater probe investigation conducted near the anticipated UDF location, and no utilities were identified. Another utility location survey will be conducted prior to field investigation activities to ensure that no utilities were added in the area since the earlier utility search.

### 3.2.5 Soils

Soils within the GE Parcel are expected to consist of some gravel and medium to fine sand. Based on publicly available web soil surveys (Natural Resources Conservation Service [NRCS] 2021), the soils originally present at the UDF site are reported to be composed of Copake fine sandy loam, Hero loam, Groton and Hinckley soils, and gravel. Despite the web soil survey indicating a larger proportion of gravel than other materials in the aforementioned composition, there is reason to believe, based on visual field operations and communication from the prior landowner (Lane), that a larger portion of finer textured material is present at the GE Parcel.

### 3.2.6 Groundwater Elevations

In fall 2019, a preliminary investigation was conducted at the GE Parcel to evaluate subsurface conditions. This investigation included geoprobes in the locations depicted on Figure 5 (discussed in Section 5.2.5). From this effort, groundwater was encountered between elevation 947 ft and 949 ft relative to National Geodetic Vertical Datum of 1929 (NGVD 29). The elevation of the water edge in the adjacent ponds was approximately 950 ft NGVD 29 at the time of the June 2010 aerial survey. Because of the granular nature of the site soils, the pond water surface elevations are likely coincident with groundwater. The nearest U.S. Geological Survey groundwater monitoring well location is approximately 1.2 miles to the northwest of the GE Parcel at latitude 42°21'04.76" and longitude 73°15'28.75". Although historical data are available for this location, they are not considered representative of site conditions for the GE Parcel considering the distance from the site and significant topographic variability in this region.

A review of Massachusetts Department of Environmental Protection (MassDEP) files uncovered an Evaluation Opinion Transmittal Report (Anonymous undated), which contains a summary of groundwater elevation data collected from monitoring wells located around the nearby Schweitzer-Mauduit and Lee Municipal Landfills. The Lee Municipal Landfill is located due south of the GE Parcel on the adjacent parcel. The report indicates that groundwater elevations in two wells (MW-84-1 and MW-94-1) along the eastern edge of the Lee Municipal Landfill (also approximately in line with the eastern edge of the GE Parcel) ranged from 955.40 ft to 959.91 ft (NGVD 29), depending on the well and gauging date. The report also indicates that groundwater elevations in three wells (MW-84-2, MW-94-2, and the MW-94-7 cluster) along the western edge of that landfill (also approximately in line with the western edge of the GE Parcel) ranged from 948.85 ft to 952.59 ft, depending on well and gauging date. These data indicate an east-to-west slope in the groundwater table.



### **3.2.7 Groundwater Quality**

There are no known data on groundwater quality within the GE Parcel. There is historical information available on bordering property; however, this information is relatively outdated.

The aforementioned Evaluation Opinion Transmittal Report includes information on groundwater quality at the Lee Municipal Landfill relative to Massachusetts groundwater standards. The report states that there is no record of oil or hazardous material being landfilled, and at the time the report was generated, the only consistent reportable concentration exceedance shown was for manganese. Because of the proximity of the Lee Municipal Landfill to the southwest of the GE Parcel, an elevated concentration of manganese in groundwater could be possible in the area between the Lee Municipal Landfill and the GE Parcel.

There are 12 U.S. Geological Survey historical groundwater wells on the southern edge of Woods Pond. There is also one groundwater well on the opposite side of Valley Street from Woods Pond and within the current mining operation property. These wells have data detailing groundwater quality; however, these data are from the early 1980s or earlier and may not be representative of current conditions.

## 4 Preliminary Conceptual UDF Design Summary

This section provides a summary of the conceptual UDF design developed to date.

### 4.1 Site Layout

As noted above, the UDF site consists of land acquired by GE from Lane that was previously part of an active sand and gravel quarry. The site will be developed to include the UDF area and UDF support area. Figure 1 depicts the boundaries of the GE Parcel, the existing features, and the conceptual design limits of the UDF area and UDF support area. It is noted that the UDF support area requirements and related facilities are not known at this time, and therefore further description of its components is not provided below. The UDF support area components and their design will be determined at a later time as part of design activities.

### 4.2 Anticipated UDF Design

The UDF will be an engineered disposal facility that will include features designed and operated to contain soils and sediments from the ROR Remedial Action, along with associated leachate, and to allow long-term monitoring following completion of filling and capping. The perimeter of the UDF will include a berm, likely constructed from on-site soil that is excavated from within the UDF limit of consolidated material. The perimeter berm will provide control of run-on from outside of the UDF limit of consolidated material and leachate from consolidated material placed within the UDF.

A double baseliner system will be installed within, and extending up against, the inside slope of the perimeter berm. The baseliner system will include primary and secondary low-permeability liners, each having maximum permeabilities of  $1 \times 10^{-7}$  cm/s and minimum thicknesses of 30 mils. A primary leachate collection system will be constructed on top of the primary liner and will drain to a sump, which will be the lowest point on the floor of the UDF. A secondary leachate collection system will be constructed between the primary and secondary liners to provide redundancy to the primary leachate collection system. The secondary leachate collection system will drain to the same sump depression as the primary system, but will be separated by the primary liner. Liquids that accumulate in the primary and secondary sumps will be removed using submersible pumps and will be stored on site in above-ground tanks prior to being taken to the GE Pittsfield Facility for treatment.

Following placement of consolidated material into the UDF, a final cover will be constructed across the limit of placement. The final cover will include a low-permeability liner with a maximum permeability of  $1 \times 10^{-7}$  cm/s and a minimum thickness of 30 mils, a drainage layer, and cover soils suitable for the establishment of vegetation. Stormwater runoff from the UDF will be managed by a system of diversion features, downchutes, culverts, and basins.

## 5 Pre-Design Investigation

Based on existing information presented in Section 3, data gaps remain in the body of knowledge needed to design, construct, and operate the UDF in accordance with the Revised Permit and current state of practice. This section describes the PDI activities that are proposed to supplement existing site information so as to support of the UDF design.

### 5.1 Data Collection Objectives

The data proposed for collection in this section will supplement data that have already been collected or are available and that are deemed applicable and of sufficient accuracy for use in the detailed design of the UDF. The activities discussed in this section will be implemented to address the data gaps or to confirm the current understanding of site conditions. Standard operating procedures to be used in the performance of PDI activities are summarized in Section 5.3.

### 5.2 Site Data Collection

The following PDI activities are proposed to address the known data gaps and are described in greater detail in the following subsections:

- Baseline habitat assessment, including a wetland survey as needed
- Topographic field survey
- Soil geotechnical investigation
- Soil environmental quality investigation
- Groundwater depth investigation
- Groundwater environmental quality investigation
- Cultural resources assessment

#### 5.2.1 Baseline Habitat Assessment

A baseline habitat assessment will be conducted to form a detailed baseline ecological inventory and assessment of existing conditions and serve as the foundation for developing the Final Cover/Closure Plan for the UDF area and UDF support area, including potential re-use of the UDF area and restoration of the UDF support area. The baseline habitat assessment of the approximately 75-acre GE Parcel will include the following components:

- The presence, location, and species composition of terrestrial and aquatic habitats will be identified initially through on-line database reviews and aerial photograph interpretation. This process will include producing cover type mapping using the community type classification mapping that was used in the Ecological Characterization of the Housatonic River (Woodlot Alternatives 2002). This mapping currently extends from the Confluence to the south end of Woods Pond, and it will be extended from that point south through the GE Parcel. The mapping will be done with the aid of aerial photographs, and these preliminary delineations will be

transferred onto the updated topographic mapping described below. Field investigations will then be conducted over the entire GE Parcel to review and verify or adjust the habitat cover type delineations.

- During the field surveys, each discrete cover type unit will be subject to a detailed inventory using the UDF/GE Parcel Habitat Inventory Form attached as Appendix A. This form will record a broad range of habitat parameters to characterize structural, physical, hydrologic, and biological conditions within each habitat cover unit. The characterization will include measurements of substrate/soil characteristics, plant species composition, a broad range of habitat features, and habitat degradation. In addition, based on the information collected, the ecological functions and values of the affected habitats will be identified and qualified.
- Aquatic resources (such as streams or potential wetlands) identified within the GE Parcel, excluding the man-made ponded areas, will be subject to field verification using current federal wetland delineation criteria. This will include completing, for those features, the U.S. Army Corps of Engineers (USACE) Wetland Determination Data Form for the Northeast Region, which is attached as Appendix B. In particular, the potential isolated scrub-shrub wetland located off Woodland Road will be evaluated using that form to determine whether it in fact constitutes a wetland.
- An evaluation will be conducted as to the presence of vernal pools at the GE Parcel through on-line aerial photography review and MNHESP database review confirmed via field verifications.
- The presence, location, and abundance of federal or state-listed threatened or endangered species or other state-listed species and their habitats will be identified through review of the USFWS on-line IPaC and review of the MNHESP records on state-listed species. In addition, GE will consult with the USFWS and MNHESP to determine whether they have any information on the existence of such species or their Priority Habitat in or near the GE Parcel. To the extent appropriate and practicable, the results of these reviews will be confirmed via field verifications. This field verification will consist of evaluating the habitat requirements of any potential state or federally listed species relative to the identified habitat characteristics on the GE Parcel.
- The presence, location, abundance, and condition of invasive species as listed by the USACE New England District or the Massachusetts Invasive Plant Advisory Group will be identified through base mapping and aerial photograph reviews in combination with field verification.

## 5.2.2 Topographic Field Survey

The latest topographic survey covering the GE Parcel was completed using aerial methods in 2010. Given limitations with the method used and the age of the survey, a new topographic survey will be conducted to accurately document existing conditions at the GE Parcel and support the detailed design of the UDF and UDF support area. Additionally, the GE Parcel includes several low areas that contain water (either groundwater or surface water or a combination of the two), for which no bottom data were collected in 2010. Consequently, the new survey will also include bathymetry across these water-containing depressions so that a continuous surface model can be created for the purposes of quantifying earthwork volumes that extend into the water-containing depressions.

The areas to be surveyed in the new topographic and bathymetric surveys are shown on Figure 2 and will encompass the portion of the GE Parcel to be developed for the UDF area and UDF support area, including peripheral areas planned to contain roads, drainage features, and utilities. The new topographic survey is anticipated to consist of either a traditional field survey, an aerial survey using Light Detection and Ranging

(LiDAR) technology, or a combination of these methods. In the event that traditional surveying methods are used, topographic shots will be collected at the following locations:

- Top and toe of slopes;
- Changes in slope gradient;
- Linear features such as fence lines, if any;
- Utilities;
- Edges of water;
- Edges of road;
- Tree lines;
- Other structures; and
- Intermediate ground shots.

Bathymetric shots will be collected on an approximately 50-foot grid and will be referenced to the same vertical datum as the land-based topographic survey. All surveying work will be performed by or under the supervision of a Professional Land Surveyor registered in the Commonwealth of Massachusetts.

### **5.2.3 Soil Geotechnical Investigation**

Soil investigations are required to support the evaluations and design of the UDF. The soil investigation program for the UDF will accomplish the following objectives:

- Characterize the variability, depth, and engineering properties of site soils.
- Collect soil data through field and laboratory testing to support and identify geotechnical design considerations, such as settlement and stability, which will be addressed in the engineering design of the UDF.
- Characterize site soils for use in construction of the UDF and operational area facilities and identification of the intended use of soils excavated for construction of the UDF and operational area facilities.

The following sections provide further details regarding the proposed boring locations and depths, soil sampling, and field and laboratory testing. This investigation program has been developed assuming that site soils are granular and are composed of sands and silty sands, which is consistent with the findings of the 2019 geoprobe investigation at the site and available subsurface information from the nearby Lee Municipal Landfill. As indicated above, requirements and facilities pertaining to the UDF support area are not known at this time. Accordingly, soil investigations for the UDF support area are not included as part of this PDI Work Plan. If deemed necessary based on design requirements for the UDF support area components, soil investigations will be proposed and conducted within the UDF support area at a later time, as outlined in the Conceptual Design Plan for the UDF.

#### **5.2.3.1 Soil Boring Program**

The proposed locations of the geotechnical borings are shown on Figure 3 and summarized in Table 1. A total of 18 borings are planned, and the borings are positioned within and outside of the anticipated UDF limits. Table 1

identifies the anticipated usage of the proposed borings. As indicated in that table, all 18 borings will be utilized for geotechnical testing purposes. Additionally, 11 of the 18 borings will also be utilized for soil quality testing purposes. Eight of the 18 borings will be utilized for the installation of temporary piezometers within and outside of the UDF footprint, as discussed in Section 5.2.5.1. Six of the 18 borings will be utilized for the installation of monitoring wells outside of the UDF footprint, as discussed in Section 5.2.5.2. The locations are based on the anticipated limits of the UDF, likely groundwater flow direction, and spatial distribution of data points across the site.

For geotechnical purposes, the borings will be advanced to a target elevation of 935 ft or lower. Where the borings will also serve as monitoring wells and temporary piezometers, the depth to groundwater also requires a minimum target depth. The deeper of the two criteria will be used when determining the minimum boring depth. Table 1 identifies the minimum depth below ground surface (bgs) for each proposed boring.

Data collected from the proposed borings will support the settlement evaluation of the UDF, the review of the liquefaction potential of the UDF foundation soils, the completion of a liquefaction analysis if required, and the stability evaluations for the final UDF buildout and any other critical interim construction phases.

Ten geotechnical borings are planned along the perimeter of the UDF. These borings will support stability evaluations of temporary excavation conditions during construction of the UDF and of the proposed UDF grading design. The perimeter borings will be spaced approximately 500 ft apart and will be located based on groundwater quality monitoring and depth-to-groundwater data needs.

It is assumed that the geotechnical borings will be completed using a drill rig mounted on an all-terrain vehicle and equipped with a 4.25-inch inner diameter hollow-stem auger. Continuous soil sampling will be performed through the first 30 ft of each boring followed by a five-foot sample interval to the boring depth. All sampling will be completed using a two-inch-diameter split-spoon sampler, with standard penetration tests (SPTs) following ASTM International (ASTM) D1586, which will be conducted for each sample collected. Soil recovered from each sample interval will be visually characterized for color, texture, and moisture content and field screened with a photoionization detector. The presence of visible staining, sheen, product, and obvious odors encountered in the soil, if any, will be noted.

Between six and eight split spoon samples from each boring will be submitted for laboratory analysis of grain size, moisture content, Atterberg limits, and specific gravity. The SPT data, field descriptions, and laboratory data will be used in the geotechnical evaluations for design of the UDF.

Arcadis U.S. Inc. (Arcadis) will supervise drilling and direct the drillers to perform SPT sampling, record blow counts on the split-spoon sampler, log the borehole, record groundwater elevations, and document details related to the advancement and sampling of each boring.

Soil cuttings will be staged on site in an appropriate waste container (e.g., roll-off, drum, lined area). Soil cuttings will be field screened for the presence of volatile organic vapors using a photoionization detector. Soil cuttings (and other investigation-derived waste) will be managed and disposed of in an appropriate manner (either on site or off site) based on the field screening results and in accordance with applicable rules and regulations.

### **5.2.3.2 Soil Testing for Engineering Properties**

The following types of soil testing will be performed through both field and laboratory means to determine the engineering properties of the site soils.

- **Standard Penetration Testing:** As discussed above, SPT sampling will be conducted during the advancement of each geotechnical boring. SPT sampling will be performed using a standard two-inch-outside-diameter split-spoon sampler, 24 inches long, and driven by a 140-pound automatic hammer with a 30-inch drop per ASTM D1586. The SPT blow count (or “N-value” term) for each sample will be recorded and will represent the number of blows required for one-foot penetration into the soil after the initial six-inch seating drive depth. The N-values will be used during the design of the UDF to estimate the engineering properties of the site soils.
- **Soil Classification:** Each sample collected from the geotechnical borings will be classified in the field through visual-manual procedures that conform to ASTM D2488 and the Arcadis Field Guide for USCS Soil Classification (Appendix C). In addition, selected samples from each boring will be submitted for laboratory classification using the Unified Soil Classification System, which is based on the soil index property tests described below and for quality control of the field classifications. The samples chosen for laboratory testing will generally focus on depths and locations within each soil layer to confirm the observed stratigraphy noted in the boring logs, within zones of loose or soft soils, and at depths below the groundwater table. Soil descriptions in the boring logs will be updated where needed to conform to the laboratory-determined soil classifications.
- **Soil Index Properties:** Soil index properties will be developed from the testing of grain size (ASTM D6913), moisture content (ASTM D2216), Atterberg limits (ASTM D4318), and specific gravity (ASTM D854). Sufficient soil from the split spoons (or from a combination of split spoons) will be provided to the selected geotechnical laboratory for completing the index property testing in accordance with the corresponding ASTM standard. The results will be used for quality control of the field soil classifications, determination of site stratigraphy, and development of engineering parameters, such as shear strength and soil elastic modulus, to support the stability and settlement evaluations. These data will also be beneficial for determining re-use criteria of excavated materials during construction of the UDF and for estimation of the permeability of the site soils.

## 5.2.4 Soil Quality Testing

Soil testing for environmental quality will be performed at each soil boring associated with a permanent monitoring well (six total) plus one soil boring associated with a temporary piezometer internal to the UDF footprint. The proposed soil borings are described in Section 5.2.3.1. Figure 4 identifies the 11 specific soil borings proposed for environmental testing. The choice of borings for environmental testing was based on the use of the monitoring wells to document long-term environmental quality before, during, and after construction of the UDF. Sampling of soil from two temporary piezometers within the UDF footprint is proposed to further document environmental quality. The environmental testing of the soils from the borings will be used to determine the presence (if any) and concentration of chemical constituents in the existing soil to establish baseline chemical conditions for comparative evaluations during UDF operations and post-closure monitoring.

At each boring location, samples will be collected at the following approximate depth intervals:

- Ground surface to a depth of 1 ft bgs, with this first depth interval obtained by manually digging at the boring location prior to commencing boring operations with the drill rig;
- 13 to 15 ft bgs;
- 28 to 30 ft bgs;



- 43 to 45 ft bgs;
- 58 to 60 ft bgs; and
- At groundwater table interface.

The actual sample depth interval and the need for additional testing at each location will be determined based on photoionization detector readings and visual observations at the time of the in-field soil investigation.

All samples will be submitted for analysis of PCBs and the full list of analytes presented in Table 2 of GE's 2013 Field Sampling Plan/Quality Assurance Project Plan (FSP/QAPP; Arcadis 2013). Although the full analyte list is recommended for establishing baseline chemical conditions, the analyte list to be used during UDF operations or long-term monitoring may be modified based on initial sampling results or the nature of the materials being disposed of.

### **5.2.5 Piezometer and Groundwater Well Installation**

A system of temporary piezometers and permanent monitoring wells will be installed in the soil borings to be advanced on the GE Parcel. The proposed soil borings are described in Section 5.3.3.1, and the specific borings to be used for piezometers (identified with a prefix of "PZ") and monitoring wells (identified with a prefix of "MW") are presented on Figure 5. Collectively, both types of features will provide groundwater data that will be used in the design of the UDF. The permanent monitoring wells may also be used for long-term monitoring of site groundwater during construction, operation, and post-closure of the UDF. As indicated above, requirements and facilities pertaining to the UDF support area are not known at this time. Accordingly, groundwater investigations for the UDF support area are not included as part of the PDI Work Plan. If deemed necessary based on design requirements for the UDF support area components, groundwater investigations will be proposed and conducted within the UDF support area at a later time, as outlined in the Conceptual Design Plan for the UDF.

#### **5.2.5.1 Temporary Piezometer Well Installation**

Eight temporary piezometers will be located within the limits of consolidated material and around the perimeter of the UDF for the purpose of gauging groundwater elevations over a limited period of time prior to the commencement of UDF construction. The temporary piezometers will supplement the permanent monitoring wells (described below) to provide a more complete and spatially disperse understanding of groundwater elevations that will be used in the design of the UDF. The proposed piezometer locations are depicted on Figure 5 and preliminary construction details are presented in Table 2. It should be noted that the preliminary information in that table is subject to change based on field conditions as observed and documented by the hydrogeologist overseeing the soil borings and piezometer/monitoring well installation. Because of their anticipated use for groundwater elevation gauging only, the piezometers will consist of one-inch-diameter casing, rather than the two-inch-diameter casing used for monitoring well construction. Following installation, the location, ground surface elevation, and top of casing elevation will be surveyed by a Professional Land Surveyor registered in the Commonwealth of Massachusetts.

#### **5.2.5.2 Permanent Monitoring Well Installation at UDF Perimeter**

Six permanent monitoring wells will be installed in selected soil borings at the perimeter of the GE Parcel, as shown on Figure 5. Preliminary construction details are presented in Table 3. It should be noted that the



preliminary information in that table is subject to change based on field conditions as observed and documented by the hydrogeologist overseeing the soil borings and piezometer/monitoring well installation. As discussed in Section 3.5, historical gauging of monitoring wells associated with the Lee Municipal Landfill to the south of the UDF indicates a generally east-to-west groundwater flow gradient. The monitoring wells are therefore positioned such that three wells (MW 2022-3, MW 2022-4, and MW 2022-5) are located along the western edge and downgradient of the UDF, one well (MW 2022-1) is located to the east and upgradient of the UDF, and two wells (MW 2022-2 and MW 2022-6) are located to the northwest and southwest and sidegradient of the UDF. The latter two wells also provide some contingency in the event groundwater flow direction has a northerly or southerly component. Finally, MW 2022-6 is positioned between the Lee Municipal Landfill and the UDF and can serve to indicate changes in groundwater quality at that location relative to the upgradient MW 2022-1 well.

The borehole depths for five of the monitoring wells are based on intercepting the estimated groundwater table at an elevation of approximately 950 ft. However, the borehole for MW 2022-4 will be advanced to a depth that is below the estimated bed elevation of the Housatonic River. Based on available on-line data, the river water surface elevation is approximately 935 ft. Because the depth of the River is unknown and possibly variable, the bottom of the borehole will be advanced to an elevation of 910 ft or lower to be conservative.

Following installation, the location, ground surface elevation, and top of casing elevation will be surveyed by a Professional Land Surveyor registered in the Commonwealth of Massachusetts.

### **5.2.6 Groundwater Depth Monitoring**

Once installed, both the temporary piezometers and monitoring wells will be gauged on a quarterly basis for a minimum of one year (a total of four events minimum) to provide a seasonal range of groundwater elevations. Prior to UDF construction, the temporary piezometers will be abandoned in place. However, the monitoring wells will remain in service for continued gauging and sampling, as discussed in Section 5.2.7.

### **5.2.7 Groundwater Testing for Environmental Quality**

Groundwater testing for environmental quality will be performed at the six permanent groundwater monitoring wells described in Section 5.2.5.2 to determine existing (baseline) groundwater chemical quality conditions for comparative evaluations during UDF operations and post-closure monitoring. Figure 6 identifies the location of the monitoring wells to be used for chemical quality testing. It should be noted that, because of their temporary nature and smaller casing diameter, none of the piezometers will be used for chemical quality testing.

Samples will be collected semi-annually for a period of two years. Samples will be submitted for analysis of the full list of analytes presented in Table 2 of the 2013 FSP/QAPP. Although the full analyte list is recommended for establishing baseline chemical conditions, the analyte list to be used during UDF operations or long-term monitoring may be modified based on initial sampling results or the nature of the materials being disposed of. Each monitoring well will also be gauged immediately prior to sampling for each event.

### **5.2.8 Phase 1A Cultural Resources Assessment**

As noted in Sections 4.2.1.7 and 4.2.2 of the Final Revised SOW, an initial Phase IA CRA of the UDF and UDF support area will be conducted separately from the CRA for the remediation areas and their associated

support areas. The initial Phase 1A CRA for the UDF area and UDF support area will include the following activities:

- An archaeological Area of Potential Effects (APE) and an historic architectural APE will be defined based on the location and extent of the UDF area and UDF support area.
- Desktop and on-line evaluations will be conducted of the Massachusetts Historical Commission's (MHC's) report files and databases, including the MACRIS, Massachusetts State Historic Preservation Plan, and MHC State Reconnaissance Survey Reports, to determine whether the UDF area or UDF support area contains or could affect cultural resources included in those databases.
- Desktop and on-line evaluations will also be conducted of the local Historic District Commission literature and databases for the same purpose.
- GE will consult with the MHC and Native American Tribal Preservation Officers regarding the locations of cultural resources and traditional cultural properties in the vicinity of the GE Parcel.
- An evaluation will be conducted of the GE Parcel, including the UDF area and UDF support area, for the potential to contain unidentified potentially significant cultural resources (i.e., whether they have no, low, or high potential to contain such resources).<sup>5</sup> This evaluation will be conducted using the approach previously developed for the 2008 Initial Phase IA CRA (URS 2008), mentioned above, which incorporated data layers for soil types, slope, land use, and the location of known archaeological sites within a GIS database. As described in that 2008 report, this approach uses the following key variables to identify the potential for an area to contain pre-contact archaeological resources:
  - **High Potential**
    - water source within 150 meters (m)
    - well drained sandy soils
    - level to fairly level topography (0 – 3%)
    - none to minimal disturbance
    - known sites in the immediate area
  - **Moderate Potential**
    - water source within 150 to 300 m
    - well drained to fairly well drained, sandy to cobbly soils
    - moderate slopes (3 – 8%)
    - minimal to moderate disturbance
    - known sites in the vicinity
  - **Low Potential**
    - water source greater than 300 m
    - poorly drained soils

---

<sup>5</sup> For purposes of these CRA evaluations, potentially significant cultural resources mean archaeological and/or historical architectural resources that are listed or could potentially meet the criteria for listing on the NRHP, resources that are listed on the Massachusetts SRHP and included on the State Inventory of Historic and Archaeological Assets, and potentially significant scientific, prehistorical, historical, or archaeological data subject to the Archaeological and Historic Preservation Act. Such resources will include properties of traditional religious and cultural importance that fall into any of the foregoing categories.

- steep slopes (> 8%)
- moderate to extensive disturbance
- no known sites in the vicinity

In addition, for historic-period archaeological sites, areas within 100 m of major historic transportation networks will be added to the high potential zone.

- Evaluation of known or suspected historic structures within the historic architectural APE will be accomplished by starting with existing historic structure inventories compiled by the MHC and local historic organizations. The locations of these structures will be plotted in the project GIS system for systematic comparison with the location of the GE Parcel. Following compilation of the existing inventory data, a reconnaissance-level windshield survey will be conducted by a qualified architectural historian to field verify the current status of each previously recorded resource, and to identify other potential historic structures within the APE.
- To the extent that the foregoing activities identify any known and potentially significant cultural resources within the archaeological APE or any known or suspected historic structures within the historic architectural APE, or indicate that the UDF area or UDF support area has a high potential to contain potentially significant cultural resources (particularly in areas not disturbed by prior operations), GE will develop and submit to EPA a supplemental plan to further evaluate whether such resources are present, including through survey activities as necessary.

## 5.3 Sampling and Analysis Procedures

The procedures to be followed in conducting the sampling and analysis and related activities described in Section 5.2 will consist of those provided in the 2013 FSP/QAPP, as applicable. Applicable standard operating procedures for field-based activities are found in Volume II of that FSP/QAPP and are listed below:

- Appendix A Soil Sampling Procedures for Analysis of Volatile Organic Chemicals (VOCs)
- Appendix C Soil Boring Installation and Soil Sampling Procedures
- Appendix D Groundwater Purging and Sampling Procedures for Monitoring Wells
- Appendix L Handling, Packing, and Shipping Procedures
- Appendix M Standard Operating Procedures for Shipment of Department of Transportation Hazardous Materials
- Appendix N Photoionization Detector Field Screening Procedures
- Appendix Q Water Level/Oil Thickness Measurement Procedures
- Appendix S Monitoring Well Installation and Development Procedures
- Appendix W Equipment Cleaning Procedures
- Appendix Y Selection of Drilling Method
- Appendix Z Monitoring Well Inventory Procedures
- Appendix GG Monitoring Well Decommissioning Procedures

In the event that the new FSP/QAPP for the ROR is has been submitted to and approved by EPA prior to initiation or during implementation of the PDI field activities for the UDF area and UDF support area, then the remaining PDI activities will be performed in accordance with that ROR FSP/QAPP.

## **5.4 Health and Safety**

The PDI field activities for the UDF area and UDF support area will be performed in accordance with the Health and Safety Plan (HASP) for the ROR (GE 2017). If an updated HASP for the ROR has been submitted to EPA prior to initiation or during implementation of the PDI field activities for the UDF area and UDF support area, the remaining PDI activities will be performed in accordance with that updated HASP.

## 6 Data Evaluation and PDI Reporting

This section describes the evaluation and reporting of data to be collected as part of the PDI.

### 6.1 Data Evaluation

Following completion of the PDI field work, laboratory analyses, and receipt of data, an evaluation will be performed of the new data along with existing data. The evaluations to be performed are dependent upon the nature of the data collected. The results of the baseline habitat assessment will be used to determine and quantify ecological conditions and functions within the UDF area and UDF support area, as well as to identify appropriate avoidance and minimization efforts that could be implemented to preserve significant or critical habitat (if any).

The topographic field survey will be combined with bathymetric survey of the water-filled depressions to yield a continuous top-of-existing-ground-surface model. The ground-surface model resulting from the PDI survey will exist digitally and will be used with earthwork modeling software for the design of the UDF area and UDF support area. It will also be used to depict existing conditions on the GE Parcel in UDF design drawings and other report figures.

The geotechnical soil investigation data will be used to derive engineering properties for site soils. These properties will be used in the UDF design to evaluate slope stability, settlement, and other geotechnical performance aspects. The soil classifications will also be used in the design of stormwater infiltration basin(s), although additional field testing may be necessary once the footprint and depth of the basin(s) are established as part of the detailed design phase. Chemical quality data for site soils and groundwater will be used to document the condition of site media prior to construction and operation of the UDF.

Groundwater elevation data will be evaluated following collection of a minimum of four quarterly rounds of monitoring well and piezometer gauging. The seasonally high groundwater elevation will be developed using the groundwater elevation in each well, modified, as appropriate, by a technical method that has been reviewed and approved by EPA using variations reported over time at other existing monitoring wells in Massachusetts. The conservative estimate of the seasonally high groundwater elevation will be used to establish the bottom elevation of the UDF (a minimum of 15 feet above the seasonally high groundwater elevation) and to evaluate slope stability. Each set of quarterly groundwater gauging data, as well as the groundwater elevation data, will also be plotted to create a series of groundwater contour maps to confirm the anticipated east-to-west groundwater gradient.

The results of the initial Phase 1A CRA will be used to assess the next steps in the process. The results of the initial Phase 1A will either result in a determination that the UDF area and UDF support area will not affect any potentially significant cultural resources (thereby satisfying the applicable or relevant and appropriate requirements relating to cultural resources), or else will be used to identify additional information needs that require further investigations, including potentially a Phase 1B archaeological or architectural field survey.

### 6.2 Reporting

As discussed in the Final Revised SOW, a UDF PDI Summary Report will be prepared following completion of the PDI. That Summary Report will:

## Pre-Design Investigation Work Plan

- Summarize the activities and investigations conducted previously as well as those performed as part of the PDI;
- Summarize the data obtained from the PDI;
- Summarize the results of the baseline habitat assessment of the UDF area and UDF support area, including an identification of the affected habitats and their functions;
- Summarize the results of the initial Phase 1A CRA of the UDF area and UDF support area, including an identification of the presence or likely presence of any potentially significant cultural resources in those areas and the need for further investigations to evaluate such resources;
- Include the other data evaluations described in Section 6.1;
- Present pertinent documentation prepared during the PDI, such as boring logs, photographs, water level measurements; and
- Present a schedule for submitting a Conceptual Design Plan for the UDF.

## 7 Schedule

The PDI data collection will be initiated following EPA's approval of this PDI Work Plan. It is noted, however, that the majority of the field work is weather-dependent and thus cannot commence until the onset of warmer weather and melting of snow and ice that may otherwise prevent site entry, obscure the ground surface, and prevent direct observation of growing season conditions.

The PDI data collection (except for the two-year groundwater quality sampling program) is anticipated to take approximately 15 months from approval of this PDI Work Plan, including the water elevation gauging of the eight temporary piezometers and the six monitoring wells for four quarters. Within 60 days after the last of these gauging events, GE will submit the UDF PDI Summary Report described in Section 6.2.

At that time, however, the second year of the two-year semi-annual groundwater quality monitoring program will not have been completed. Accordingly, those final two events will subsequently be completed; and GE will, within 60 days after receipt of the results from the last such event, submit an addendum to the UDF PDI Summary Report to document the results from the second year of groundwater testing.

## 8 References

- Anchor QEA, LLC, AECOM, and Arcadis. 2021. Final Revised Rest of River Statement of Work. Prepared for General Electric Company, Pittsfield, Massachusetts. September. Available online at <https://semspub.epa.gov/work/01/659938.pdf>
- Anonymous. Undated. LSP Evaluation Opinion Lee Landfill. Obtained May 2008 from MassDEP file review.
- Arcadis. 2013. Field Sampling Plan/Quality Assurance Project Plan, Revision 5, Volumes I, II, and III. Prepared for General Electric Company, Pittsfield, Massachusetts. July 2. Available online at: <https://semspub.epa.gov/work/01/540450.pdf>, <https://semspub.epa.gov/work/01/540451.pdf>, and <https://semspub.epa.gov/work/01/540452.pdf>.
- EPA. 2020. Revised Final Permit Modification to the 2016 Reissued RCRA Permit and Selection of CERCLA Remedial Action and Operation & Maintenance for Rest of River. December 16. Available online at: <https://semspub.epa.gov/work/01/650440.pdf>.
- FEMA. 1982a. Flood Insurance Rate Map, Town of Lee, Massachusetts, Berkshire County Community Panel Number 250028 0003 B. June 1.
- FEMA. 1982b. Flood Insurance Rate Map, Town of Lee, Massachusetts, Berkshire County Community Panel Number 250028 0007 B. June 1.
- GE. 2017. Health and Safety Plan, GE-Pittsfield/Housatonic River Site – Rest of River. September 8. for General Electric Company, Pittsfield, Massachusetts. Available online at: <https://semspub.epa.gov/work/01/622332.pdf>.
- Natural Resources Conservation Service. 2021. *Web Soil Survey*. Retrieved October 2021 from <https://websoilsurvey.sc.egov.usda.gov/App/HomePage.htm>.
- URS. 2008. Initial Phase IA Cultural Resources Assessment for the Housatonic River – Rest of River Project. Prepared for General Electric Company, Pittsfield, Massachusetts. March 20; Public Release Version submitted on April 3, 2008.
- U.S. Fish and Wildlife Service. 2021. *Information for Planning and Consultation*. Retrieved October 2021 from <https://ecos.fws.gov/ipac/>.
- Woodlot Alternatives, Inc. 2002. *Ecological Characterization of the Housatonic River*. Prepared for EPA Region 1, September.



# Tables

**Table 1**  
**Proposed Soil Boring Details**  
**Pre-Design Investigation Work Plan**  
**Upland Disposal Facility**  
**General Electric Company - Pittsfield, Massachusetts**



Boring ID	Anticipated Use				Coordinates (NAD 83 State Plane, US ft)		Ex. Ground El. (ft, NGVD 29)	Min. Btm. Boring Depth (ft Below Ground Surface)
	Soil Geotechnical Data	Soil Environmental Data	Monitoring Well	Temporary Piezometer	Northing	Easting		
MW 2022-1	X	X	X		2,954,259.2	187,006.6	1,037.1	93.1
MW 2022-2	X	X	X		2,955,026.6	186,248.6	989.9	45.9
MW 2022-3	X	X	X		2,954,723.7	185,960.9	955.0	11.0
MW 2022-4	X	X	X		2,954,209.5	186,347.0	1,028.4	84.4
MW 2022-5	X	X	X		2,953,739.3	186,064.6	1,005.0	61.0
MW 2022-6	X	X	X		2,953,267.3	186,393.2	1,029.8	85.8
PZ 2022-1	X	X		X	2,954,941.5	186,656.6	995.0	51.0
PZ 2022-2	X	X		X	2,954,588.0	186,497.2	998.7	54.7
PZ 2022-3	X	X		X	2,954,622.3	186,844.2	1,035.2	91.2
PZ 2022-4	X	X		X	2,954,209.5	186,347.0	1,022.5	78.5
PZ 2022-5	X			X	2,954,154.1	186,703.0	1,035.0	91.0
PZ 2022-6	X			X	2,953,770.5	186,503.8	990.0	46.0
PZ 2022-7	X			X	2,953,872.7	186,980.9	1,033.9	89.8
PZ 2022-8	X	X		X	2,953,539.2	186,870.2	1,036.6	92.6
B 2022-1	X				2,954,035.2	186,569.6	1,029.0	94.0
B 2022-2	X				2,954,354.1	186,496.2	1,034.2	99.2
B 2022-3	X				2,954,487.0	186,219.7	997.2	62.2
B 2022-4	X				2,954,867.3	186,397.4	989.7	54.7

**Notes:**

- Existing ground elevation at each boring location is based on June 2010 survey by SK Design Group, Inc..
- Following installation, each boring location will be field surveyed to document installed coordinates, ground elevation adjacent to the well casing, and elevation of top of well casing.
- In general, minimum bottom of boring is based on advancing to at least 1 foot below the bottom of the anticipated screen interval for borings to be used for temporary piezometers or monitoring wells. Minimum bottom of boring for MW 2022-4 is based on reaching a target elevation of 910 ft or lower, which is anticipated to be below the bed of the downgradient Housatonic River. Minimum bottom of boring for soil geotechnical data purposes only is based on advancing to el. 935 ft or lower.

**Table 2**  
**Proposed Temporary Piezometer Construction Details**  
**Pre-Design Investigation Work Plan**  
**Upland Disposal Facility**  
**General Electric Company - Pittsfield, Massachusetts**



Piezometer ID	Coordinates (NAD 83 State Plane, US ft)		Elevations (ft, NGVD 29)			Depths (ft Below Ground Surface)	
	Northing	Easting	Ex. Ground	Estimated GW El.	Well Screen Interval	Depth to GW	Min. Btm. Boring
PZ 2022-1	2,954,941.5	186,656.6	995.0	950	945 - 955	45.0	51.0
PZ 2022-2	2,954,588.0	186,497.2	998.7	950	945 - 955	48.7	54.7
PZ 2022-3	2,954,622.3	186,844.2	1,035.2	950	945 - 955	85.2	91.2
PZ 2022-4	2,954,209.5	186,347.0	1,022.5	950	945 - 955	72.5	78.5
PZ 2022-5	2,954,154.1	186,703.0	1,035.0	950	945 - 955	85.0	91.0
PZ 2022-6	2,953,770.5	186,503.8	990.0	950	945 - 955	40.0	46.0
PZ 2022-7	2,953,872.7	186,980.9	1,033.9	950	945 - 955	83.8	89.8
PZ 2022-8	2,953,539.2	186,870.2	1,036.6	950	945 - 955	86.6	92.6

**Notes:**

1. Existing ground elevation at each piezometer is based on June 2010 survey by SK Design Group, Inc..
2. Following installation, each piezometer will be field surveyed to document installed coordinates, ground elevation adjacent to the piezometer casing, and elevation of top of piezometer casing.
3. Groundwater elevation listed is estimated based on available information. Indicated screen interval is intended to bracket the groundwater elevation and may be modified based on groundwater elevation at time of piezometer installation.
4. Minimum bottom of boring is based on advancing to at least 1 foot below the bottom of the indicated screen interval.

**Table 3**  
**Proposed Monitoring Well Construction Details**  
**Pre-Design Investigation Work Plan**  
**Upland Disposal Facility**  
**General Electric Company - Pittsfield, Massachusetts**



Monitoring Well ID	Anticipated Use in Monitoring Program	Coordinates (NAD 83 State Plane, US ft)		Elevations (ft, NGVD 29)			Depths (ft Below Ground Surface)	
		Northing	Easting	Ex. Ground	Estimated GW El.	Well Screen Interval	Depth to GW	Min. Btm. Boring
MW 2022-1	Upgradient (Background)	2,954,259.2	187,006.6	1,037.1	950	945 - 955	87.1	93.1
MW 2022-2	Sidegradient	2,955,026.6	186,248.6	989.9	950	945 - 955	39.9	45.9
MW 2022-3	Downgradient	2,954,723.7	185,960.9	955.0	950	945 - 955	5.0	11.0
MW 2022-4	Downgradient	2,954,335.2	185,913.9	1,028.4	950	945 - 955	78.4	84.4
MW 2022-5	Downgradient	2,953,739.3	186,064.6	1,005.0	950	945 - 955	55.0	61.0
MW 2022-6	Sidegradient	2,953,267.3	186,393.2	1,029.8	950	945 - 955	79.8	85.8

**Notes:**





1. Existing ground elevation at each well is based on June 2010 survey by SK Design Group, Inc..
2. Following installation, each well will be field surveyed to document installed coordinates, ground elevation adjacent to the well casing, and elevation of top of well casing.
3. Groundwater elevation listed is estimated based on available information. Indicated screen interval is intended to bracket the groundwater elevation and may be modified based on groundwater elevation at time of well installation.
4. Minimum bottom of boring is based on advancing to at least 1 foot below the bottom of the indicated screen interval.

# Figures





## A horizontal graphic scale bar. It is divided into four equal segments. The first segment is black, the second is white, the third is black, and the fourth is white. Above the bar, the number '0' is at the left end, '500'' is at the boundary between the third and fourth segments, and '1000'' is at the right end. Below the bar, the text 'GRAPHIC SCALE' is centered.

- |   |  |
|---|--|
|  | GE PARCEL BOUNDARY                                       |
|  | UPLAND DISPOSAL FACILITY LIMITS OF CONSOLIDATED MATERIAL |
|  | UPLAND DISPOSAL FACILITY OPERATIONAL AREA                |
|  | POTENTIAL UPLAND DISPOSAL FACILITY SUPPORT AREA          |

1. SITE FEATURES OBTAINED FROM DRAWING ENTITLED "PLAN OF LAND SURVEYED FOR THE LANE CONSTRUCTION CORPORATION" PREPARED BY SK DESIGN GROUP, INC., DATED JUNE 4, 2010.
2. AERIAL IMAGERY WAS OBTAINED VIA GOOGLE EARTH DATED 10/04/2018, ACCESSED 09/22/2021.
3. UPLAND DISPOSAL FACILITY LIMITS OF CONSOLIDATED MATERIAL, OPERATIONAL AREA, AND SUPPORT AREAS SHOWN ARE CONCEPTUAL ONLY.


GENERAL ELECTRIC COMPANY  
PITTSFIELD, MASSACHUSETTS  
**HOUSATONIC RIVER**

## SITE PLAN



FIGURE  
1






#### LEGEND:

- GE PARCEL BOUNDARY
- UPLAND DISPOSAL FACILITY LIMITS OF CONSOLIDATED MATERIAL
- UPLAND DISPOSAL FACILITY OPERATIONAL AREA
- POTENTIAL UPLAND DISPOSAL FACILITY SUPPORT AREA

#### NOTES:

1. SITE FEATURES OBTAINED FROM DRAWING ENTITLED "PLAN OF LAND SURVEYED FOR THE LANE CONSTRUCTION CORPORATION" PREPARED BY SK DESIGN GROUP, INC., DATED JUNE 4, 2010.
2. AERIAL IMAGERY WAS OBTAINED VIA GOOGLE EARTH DATED 10/04/2018, ACCESSED 09/22/2021.
3. EXTENTS OF BATHYMETRIC SURVEY AREAS ARE APPROXIMATE AND ARE DEPENDENT ON WATER LEVEL AT TIME OF SURVEY.
4. UPLAND DISPOSAL FACILITY LIMITS OF CONSOLIDATED MATERIAL, OPERATIONAL AREA, AND SUPPORT AREAS SHOWN ARE CONCEPTUAL ONLY.



GENERAL ELECTRIC COMPANY  
PITTSFIELD, MASSACHUSETTS  
HOUSATONIC RIVER


## PROPOSED FIELD SURVEY ACTIVITIES




FIGURE

2
















**LEGEND:**

-  GE PARCEL BOUNDARY  
 UPLAND DISPOSAL FACILITY  
 LIMITS OF CONSOLIDATED  
 MATERIAL  
 UPLAND DISPOSAL FACILITY  
 OPERATIONAL AREA  
 POTENTIAL UPLAND DISPOSAL FACILITY SUPPORT AREA  
 HISTORICAL GEOPROBE LOCATIONS  
 PROPOSED SOIL BORINGS WITH SOIL QUALITY SAMPLING  
 PROPOSED SOIL BORINGS (NO SOIL QUALITY SAMPLING)

**NOTES:**

1. SITE FEATURES OBTAINED FROM DRAWING ENTITLED "PLAN OF LAND SURVEYED FOR THE LANE CONSTRUCTION CORPORATION" PREPARED BY SK DESIGN GROUP, INC., DATED JUNE 4, 2010.
2. AERIAL IMAGERY WAS OBTAINED VIA GOOGLE EARTH DATED 10/04/2018, ACCESSED 09/22/2021.
3. UPLAND DISPOSAL FACILITY LIMITS OF CONSOLIDATED MATERIAL, OPERATIONAL AREA, AND SUPPORT AREAS SHOWN ARE CONCEPTUAL ONLY.

GENERAL ELECTRIC COMPANY  
PITTSFIELD, MASSACHUSETTS  
**HOUSATONIC RIVER**


## PROPOSED SOIL QUALITY INVESTIGATION




FIGURE

4









# Appendix A

## UDF/GE Parcel Habitat Inventory Form

**General Electric Housatonic Rest of River  
Upland Disposal Facility and GE Parcel Habitat Inventory Form**

**I. General Information**

Site Name

Location/Physical Description

Date(s) of Site Visit(s) and Data Collection

Weather Conditions During Site Visit

Field Staff Performing Evaluation

Date this form was completed

**II. Site Description**

**A. Hydrology/Water Regime**

- |   |   |
|---|---|
| <input type="checkbox"/> Permanently flooded      | <input type="checkbox"/> Saturated              |
| <input type="checkbox"/> Intermittently exposed   | <input type="checkbox"/> Temporarily flooded    |
| <input type="checkbox"/> Semi-permanently flooded | <input type="checkbox"/> Intermittently flooded |
| <input type="checkbox"/> Seasonally flooded       | <input type="checkbox"/> Artificially flooded   |
| <input type="checkbox"/> Upland                   |   |

**B. Community Cover Type(s)**

**Wetland**

- ☐ Transitional floodplain forest
- ☐ High terrace floodplain forest
- ☐ Red maple swamp
- ☐ Vernal pool
- ☐ Black ash-red maple-tamarack calcareous seepage swamp
- ☐ Deep emergent marsh
- ☐ Shallow emergent marsh
- ☐ Shrub swamp
- ☐ Wet meadow

**Upland**

- ☐ Northern Hardwoods-Hemlock-White Pine Forest
- ☐ Rich mesic forest
- ☐ Red Oak-Sugar Maple Transition Forest
- ☐ Agricultural fields
- ☐ Cultural grassland
- ☐ Successional northern hardwoods
- ☐ Spruce-fir-northern hardwood forest
- ☐ Developed/disturbed cover types
- ☐

**Bordering Riverine/Aquatic Habitat**

- |   |  |
|---|--|
| <input type="checkbox"/> High-gradient stream   | <input type="checkbox"/> Low-gradient stream           |
| <input type="checkbox"/> Medium-gradient stream | <input type="checkbox"/> Moderately alkaline lake/pond |

General Electric Housatonic Rest of River  
Upland Disposal Facility and GE Parcel Habitat Inventory Form

☐ Backwater

☐

C. Inventory (Plant community)

% Cover:

Trees (> 20')

Shrubs (< 20')

Woody vines

Mosses

Herbaceous

Plant Lists (species that comprise 10% or more of the vegetative cover in each strata; “\*” designates a dominant plant species for the strata):

Strata	Plant Species	Strata	Plant Species

D. Inventory (Soils)

Soil Survey Unit

Drainage Class

Texture (upper part)

Depth

Representative Soil Pit Log

Soil Horizon	Depth (inches)	Color	Soil Texture	Mottling
Notes:				

III. Important Habitat Features

Wildlife Food

Important Wetland/Aquatic Food Plants (smartweeds, pondweeds, wild rice, bulrush, wild celery)

☐ Abundant

☐ Present

☐ Absent

☐ Not Applicable

Important Upland/Wetland Food Plants (hard mast and fruit/berry producers)

**General Electric Housatonic Rest of River  
Upland Disposal Facility and GE Parcel Habitat Inventory Form**

☐ Abundant                      ☐ Present                      ☐ Absent                      ☐ Not Applicable

Shrub thickets or streambeds with abundant earthworms (American woodcock)

☐ Abundant                      ☐ Present                      ☐ Absent                      ☐ Not Applicable

Cover/Perches/Basking/Denning/Nesting Habitat

Shrub and/or herbaceous vegetation suitable for veery nesting

☐ Abundant                      ☐ Present                      ☐ Absent                      ☐ Not Applicable

Trees (live or dead) > 30" DBH

☐ Abundant                      ☐ Present                      ☐ Absent                      ☐ Not Applicable

Standing Dead Trees (potential for cavities and perches):

☐ Abundant                      ☐ Present                      ☐ Absent                      ☐ Not Applicable

Tree Cavities in trunks or limbs:

☐ Abundant                      ☐ Present                      ☐ Absent                      ☐ Not Applicable

Small mammal burrows:

☐ Abundant                      ☐ Present                      ☐ Absent                      ☐ Not Applicable

Dense herbaceous cover (voles, small mammals, amphibians & reptiles)

☐ Abundant                      ☐ Present                      ☐ Absent                      ☐ Not Applicable

Large woody debris on the ground (small mammals, mink, amphibians & reptiles)

☐ Abundant                      ☐ Present                      ☐ Absent                      ☐ Not Applicable

Rocks, crevices, logs, tree roots or hummocks under water's surface (turtles, snakes, frogs)

☐ Abundant                      ☐ Present                      ☐ Absent                      ☐ Not Applicable

Rocks, crevices, fallen logs, overhanging branches or hummocks at, or within 1m above the water's surface (turtles, snakes, frogs, wading birds, wood duck, mink, raccoon)

☐ Abundant                      ☐ Present                      ☐ Absent                      ☐ Not Applicable

Rock piles, crevices, or hollow logs suitable for:

☐ otter                      ☐ mink                      ☐ porcupine                      ☐ bear                      ☐ bobcat                      ☐ turkey vulture

Live or dead standing vegetation overhanging water or offering good visibility of open water (e.g., osprey, kingfisher, flycatchers, cedar waxwings)

☐ Abundant                      ☐ Present                      ☐ Absent                      ☐ Not Applicable

Depressions that may serve as seasonal (vernal/autumnal) pools

☐ Abundant                      ☐ Present                      ☐ Absent                      ☐ Not Applicable

Standing water present at least part of the growing season, suitable for use by



**General Electric Housatonic Rest of River  
Upland Disposal Facility and GE Parcel Habitat Inventory Form**

- |  |   |
|--|---|
| <input type="checkbox"/> Breeding amphibians | <input type="checkbox"/> Non-breeding amphibians (foraging, re-hydration) |
| <input type="checkbox"/> Turtles             | <input type="checkbox"/> Foraging waterfowl                               |

Sphagnum hummocks or mats, moss-covered logs or saturated logs, overhanging or directly adjacent to pools of standing water in spring (four-toed salamander)

- |                                   |                                  |                                 |   |
|-----------------------------------|----------------------------------|---------------------------------|---|
| <input type="checkbox"/> Abundant | <input type="checkbox"/> Present | <input type="checkbox"/> Absent | <input type="checkbox"/> Not Applicable |
|-----------------------------------|----------------------------------|---------------------------------|---|

Important habitat characteristics

Medium to large (> 6"), flat rocks within a stream (cover for stream salamanders and nesting habitat for spring & two-lined salamanders)

- |                                   |                                  |                                 |   |
|-----------------------------------|----------------------------------|---------------------------------|---|
| <input type="checkbox"/> Abundant | <input type="checkbox"/> Present | <input type="checkbox"/> Absent | <input type="checkbox"/> Not Applicable |
|-----------------------------------|----------------------------------|---------------------------------|---|

Flat rocks and logs on banks or within exposed portions of streambeds (cover for stream salamanders and nesting habitat for dusky salamanders)

- |                                   |                                  |                                 |   |
|-----------------------------------|----------------------------------|---------------------------------|---|
| <input type="checkbox"/> Abundant | <input type="checkbox"/> Present | <input type="checkbox"/> Absent | <input type="checkbox"/> Not Applicable |
|-----------------------------------|----------------------------------|---------------------------------|---|

Underwater banks of fine silt and/or clay (beaver, muskrat, otter)

- |                                   |                                  |                                 |   |
|-----------------------------------|----------------------------------|---------------------------------|---|
| <input type="checkbox"/> Abundant | <input type="checkbox"/> Present | <input type="checkbox"/> Absent | <input type="checkbox"/> Not Applicable |
|-----------------------------------|----------------------------------|---------------------------------|---|

Undercut or overhanging banks (small mammals, mink, weasels)

- |                                   |                                  |                                 |   |
|-----------------------------------|----------------------------------|---------------------------------|---|
| <input type="checkbox"/> Abundant | <input type="checkbox"/> Present | <input type="checkbox"/> Absent | <input type="checkbox"/> Not Applicable |
|-----------------------------------|----------------------------------|---------------------------------|---|

Vertical sandy banks (bank swallow, kingfisher)

- |                                   |                                  |                                 |   |
|-----------------------------------|----------------------------------|---------------------------------|---|
| <input type="checkbox"/> Abundant | <input type="checkbox"/> Present | <input type="checkbox"/> Absent | <input type="checkbox"/> Not Applicable |
|-----------------------------------|----------------------------------|---------------------------------|---|

Areas of ice-free open water in winter

- |                                   |                                  |                                 |   |
|-----------------------------------|----------------------------------|---------------------------------|---|
| <input type="checkbox"/> Abundant | <input type="checkbox"/> Present | <input type="checkbox"/> Absent | <input type="checkbox"/> Not Applicable |
|-----------------------------------|----------------------------------|---------------------------------|---|

Mud flats

- |                                   |                                  |                                 |   |
|-----------------------------------|----------------------------------|---------------------------------|---|
| <input type="checkbox"/> Abundant | <input type="checkbox"/> Present | <input type="checkbox"/> Absent | <input type="checkbox"/> Not Applicable |
|-----------------------------------|----------------------------------|---------------------------------|---|

Exposed areas of well-drained, sandy soil suitable for turtle nesting

- |                                   |                                  |                                 |   |
|-----------------------------------|----------------------------------|---------------------------------|---|
| <input type="checkbox"/> Abundant | <input type="checkbox"/> Present | <input type="checkbox"/> Absent | <input type="checkbox"/> Not Applicable |
|-----------------------------------|----------------------------------|---------------------------------|---|

Wildlife dens/nests (if observed)

Turtle nesting sites

- |                                   |                                  |                                 |   |
|-----------------------------------|----------------------------------|---------------------------------|---|
| <input type="checkbox"/> Abundant | <input type="checkbox"/> Present | <input type="checkbox"/> Absent | <input type="checkbox"/> Not Applicable |
|-----------------------------------|----------------------------------|---------------------------------|---|

Bank swallow colony

- |                                   |                                  |                                 |   |
|-----------------------------------|----------------------------------|---------------------------------|---|
| <input type="checkbox"/> Abundant | <input type="checkbox"/> Present | <input type="checkbox"/> Absent | <input type="checkbox"/> Not Applicable |
|-----------------------------------|----------------------------------|---------------------------------|---|

Nest(s) present of	<input type="checkbox"/> Bald Eagle	<input type="checkbox"/> Osprey	<input type="checkbox"/> Great Blue Heron
--------------------	-------------------------------------	---------------------------------	---

Den(s) present of	<input type="checkbox"/> Otter	<input type="checkbox"/> Mink	<input type="checkbox"/> Beaver
-------------------	--------------------------------	-------------------------------	---------------------------------



**General Electric Housatonic Rest of River  
Upland Disposal Facility and GE Parcel Habitat Inventory Form**

Emergent Wetlands (if Applicable)

Emergent wetland vegetation at least seasonally flooded during the growing season (wood duck, green heron, black-crowned night heron, king rail, Virginia rail, coot, etc.)

Flooded > 5 cm ☐ Present ☐ Absent

Flooded > 25 cm (pied-billed grebe) ☐ Present ☐ Absent

Persistent emergent wetland vegetation at least seasonally flooded during the growing season (mallard, American bittern, sora, common snipe, red-winged blackbird, swamp sparrow, marsh wren)

Flooded > 5 cm ☐ Present ☐ Absent

Flooded > 25 cm (least bittern, common moorhen) ☐ Present ☐ Absent

Cattail emergent wetland vegetation at least seasonally flooded during the growing season

Flooded > 5 cm (marsh wren) ☐ Present ☐ Absent

Flooded > 25 cm (least bittern, common moorhen) ☐ Present ☐ Absent

Fine-leaved emergent vegetation (grasses and sedges) at least seasonally flooded during the growing season (common snipe, spotted sandpiper, sedge wren)

Flooded > 5 cm ☐ Present ☐ Absent

Flooded > 25 cm (least bittern, common moorhen) ☐ Present ☐ Absent

**IV. Habitat Degradation**

☐ Evidence of significant levels of dumping

☐ Evidence of significant erosion or sedimentation problems

☐ Significant invasion of exotic plants (e.g., purple loosestrife, *Phragmites*, glossy buckthorn)

☐ Disturbance from roads or highways ☐ Evidence of fire

☐ Evidence of other human disturbance

# Appendix B

**USACE Wetland Determination Data Form for the Northeast  
Region**

## WETLAND DETERMINATION DATA FORM – Northcentral and Northeast Region

Project/Site: \_\_\_\_\_ City/County: \_\_\_\_\_ Sampling Date: \_\_\_\_\_

Applicant/Owner: \_\_\_\_\_ State: \_\_\_\_\_ Sampling Point: \_\_\_\_\_

Investigator(s): \_\_\_\_\_ Section, Township, Range: \_\_\_\_\_

Landform (hillslope, terrace, etc.): \_\_\_\_\_ Local relief (concave, convex, none): \_\_\_\_\_ Slope (%): \_\_\_\_\_

Subregion (LRR or MLRA): \_\_\_\_\_ Lat: \_\_\_\_\_ Long: \_\_\_\_\_ Datum: \_\_\_\_\_

Soil Map Unit Name: \_\_\_\_\_ NWI classification: \_\_\_\_\_

Are climatic / hydrologic conditions on the site typical for this time of year? Yes \_\_\_\_\_ No \_\_\_\_\_ (If no, explain in Remarks.)

Are Vegetation \_\_\_\_\_, Soil \_\_\_\_\_, or Hydrology \_\_\_\_\_ significantly disturbed? Are "Normal Circumstances" present? Yes \_\_\_\_\_ No \_\_\_\_\_

Are Vegetation \_\_\_\_\_, Soil \_\_\_\_\_, or Hydrology \_\_\_\_\_ naturally problematic? (If needed, explain any answers in Remarks.)

### SUMMARY OF FINDINGS – Attach site map showing sampling point locations, transects, important features, etc.

Hydrophytic Vegetation Present? Yes _____ No _____	<b>Is the Sampled Area within a Wetland?</b> Yes _____ No _____ If yes, optional Wetland Site ID: _____
Hydric Soil Present? Yes _____ No _____	
Wetland Hydrology Present? Yes _____ No _____	
Remarks: (Explain alternative procedures here or in a separate report.)	

### HYDROLOGY

Wetland Hydrology Indicators:		Secondary Indicators (minimum of two required)
<u>Primary Indicators (minimum of one is required; check all that apply)</u>		____ Surface Soil Cracks (B6)
____ Surface Water (A1)	____ Water-Stained Leaves (B9)	____ Drainage Patterns (B10)
____ High Water Table (A2)	____ Aquatic Fauna (B13)	____ Moss Trim Lines (B16)
____ Saturation (A3)	____ Marl Deposits (B15)	____ Dry-Season Water Table (C2)
____ Water Marks (B1)	____ Hydrogen Sulfide Odor (C1)	____ Crayfish Burrows (C8)
____ Sediment Deposits (B2)	____ Oxidized Rhizospheres on Living Roots (C3)	____ Saturation Visible on Aerial Imagery (C9)
____ Drift Deposits (B3)	____ Presence of Reduced Iron (C4)	____ Stunted or Stressed Plants (D1)
____ Algal Mat or Crust (B4)	____ Recent Iron Reduction in Tilled Soils (C6)	____ Geomorphic Position (D2)
____ Iron Deposits (B5)	____ Thin Muck Surface (C7)	____ Shallow Aquitard (D3)
____ Inundation Visible on Aerial Imagery (B7)	____ Other (Explain in Remarks)	____ Microtopographic Relief (D4)
____ Sparsely Vegetated Concave Surface (B8)		____ FAC-Neutral Test (D5)
<b>Field Observations:</b>		<b>Wetland Hydrology Present?</b> Yes _____ No _____
Surface Water Present? Yes _____ No _____ Depth (inches): _____	Water Table Present? Yes _____ No _____ Depth (inches): _____	
Saturation Present? Yes _____ No _____ Depth (inches): _____ (includes capillary fringe)		
Describe Recorded Data (stream gauge, monitoring well, aerial photos, previous inspections), if available:		
Remarks:		

**VEGETATION – Use scientific names of plants.**

Sampling Point: \_\_\_\_\_

Tree Stratum (Plot size: _____ )	Absolute % Cover	Dominant Species?	Indicator Status	
1. _____	_____	_____	_____	<b>Dominance Test worksheet:</b> Number of Dominant Species That Are OBL, FACW, or FAC: _____ (A)  Total Number of Dominant Species Across All Strata: _____ (B)  Percent of Dominant Species That Are OBL, FACW, or FAC: _____ (A/B)
2. _____	_____	_____	_____	
3. _____	_____	_____	_____	
4. _____	_____	_____	_____	
5. _____	_____	_____	_____	
6. _____	_____	_____	_____	
7. _____	_____	_____	_____	
_____ = Total Cover				<b>Prevalence Index worksheet:</b> <div style="display: flex; justify-content: space-between;"> <span>Total % Cover of: _____</span> <span>Multiply by: _____</span> </div> OBL species _____ x 1 = _____ FACW species _____ x 2 = _____ FAC species _____ x 3 = _____ FACU species _____ x 4 = _____ UPL species _____ x 5 = _____ Column Totals: _____ (A) _____ (B)  Prevalence Index = B/A = _____
Sapling/Shrub Stratum (Plot size: _____ )				
1. _____	_____	_____	_____	
2. _____	_____	_____	_____	
3. _____	_____	_____	_____	
4. _____	_____	_____	_____	
5. _____	_____	_____	_____	
6. _____	_____	_____	_____	
7. _____	_____	_____	_____	
_____ = Total Cover				
Herb Stratum (Plot size: _____ )				<b>Hydrophytic Vegetation Indicators:</b> ___ 1 - Rapid Test for Hydrophytic Vegetation ___ 2 - Dominance Test is >50% ___ 3 - Prevalence Index is ≤3.0 <sup>1</sup> ___ 4 - Morphological Adaptations <sup>1</sup> (Provide supporting data in Remarks or on a separate sheet) ___ Problematic Hydrophytic Vegetation <sup>1</sup> (Explain)  <sup>1</sup> Indicators of hydric soil and wetland hydrology must be present, unless disturbed or problematic.
1. _____	_____	_____	_____	
2. _____	_____	_____	_____	
3. _____	_____	_____	_____	
4. _____	_____	_____	_____	
5. _____	_____	_____	_____	
6. _____	_____	_____	_____	
7. _____	_____	_____	_____	
8. _____	_____	_____	_____	
9. _____	_____	_____	_____	
10. _____	_____	_____	_____	
11. _____	_____	_____	_____	
12. _____	_____	_____	_____	
_____ = Total Cover				
Woody Vine Stratum (Plot size: _____ )				<b>Definitions of Vegetation Strata:</b>  <b>Tree</b> – Woody plants 3 in. (7.6 cm) or more in diameter at breast height (DBH), regardless of height.  <b>Sapling/shrub</b> – Woody plants less than 3 in. DBH and greater than or equal to 3.28 ft (1 m) tall.  <b>Herb</b> – All herbaceous (non-woody) plants, regardless of size, and woody plants less than 3.28 ft tall.  <b>Woody vines</b> – All woody vines greater than 3.28 ft in height.
1. _____	_____	_____	_____	
2. _____	_____	_____	_____	
3. _____	_____	_____	_____	
4. _____	_____	_____	_____	
_____ = Total Cover				
Remarks: (Include photo numbers here or on a separate sheet.)				<b>Hydrophytic Vegetation Present?</b> Yes _____ No _____

## SOIL

Sampling Point: \_\_\_\_\_

[illegible]

# Appendix C

## Arcadis Field Guide for USCS Soil Classification

# FIELD GUIDE FOR USCS SOIL CLASSIFICATION

SEPTEMBER 1, 2020; REV 0



## Color Examples:

	Medium Bluish Gray (5B 5/1)
	Brownish Gray (5YR 4/1)
	Light Olive Brown (5Y 5/6)
	Light Olive (10Y 5/4)
	Grayish Olive (10Y 4/2)
	Grayish Brown (5YR 3/2)
	Pale Red (5R 6/2)
	Dark Reddish-Brown (10R 3/4)
	Light Brown (5YR 6/4)
	Moderate Red (5R 4/6)
	Moderate Reddish-Brown (10R 4/6)
	Pale Yellowish Orange (10YR 8/6)
	Moderate Yellowish Brown (10YR 5/4)
	Moderate Reddish Orange (10R 6/6)
	Grayish Yellow (5Y 8/4)

Colors may vary slightly due to reproduction

## Description Format:

1. USCS Group Name (USCS Group Symbol);	5. minor constituents,
2. density/consistency,	6. moisture,
3. color,	7. additional details,
4. major constituents,	8. [geologic origin] (eg fill, alluvium, etc)

\* Major/minor constituent descriptions should include particle size range and angularity for granular soils and plasticity for fine-grained soils.

## Example Descriptions:

- Lean Clay with Sand (CL); Very stiff, dark gray, medium plasticity fines, coarse, angular sand, trace gravel, moist [levee fill]
- Well-Graded Sand with Silt (SW-SM); Medium dense, brown, subangular sand, low plasticity fines, moist, slightly organic [holocene terrace deposits]

## Coarse-Grained Soil Flow Chart

		Group Symbol		Group Name	
% gravel > % sand	≤5% fines	Well-graded		GW	<15% sand well-graded gravel
		Poorly graded		GP	≥15% sand well-graded gravel with sand
	5%-15% fines	Well-graded	silt fines	GW-GM	<15% sand well-graded gravel with silt
			clay fines	GW-GC	≥15% sand well-graded gravel with silt and sand
		Poorly graded	silt fines	GP-GM	<15% sand well-graded gravel with clay
			clay fines	GP-GC	≥15% sand well-graded gravel with clay and sand
	≥15% fines	silt fines		GM	<15% sand poorly-graded gravel with silt
		clay fines		GC	≥15% sand poorly-graded gravel with silt and sand
	% sand > % gravel	Well-graded		SW	<15% sand poorly-graded gravel with clay
		Poorly graded		SP	≥15% sand poorly-graded gravel with clay and sand
	5%-15% fines	Well-graded	silt fines	SW-SM	<15% gravel well-graded sand
			clay fines	SW-SC	≥15% gravel well-graded sand with gravel
		Poorly graded	silt fines	SP-SM	<15% gravel poorly-graded sand
			clay fines	SP-SC	≥15% gravel poorly-graded sand with gravel
	≥15% fines	silt fines		SM	<15% gravel poorly-graded sand with silt
		clay fines		SC	≥15% gravel poorly-graded sand with silt and gravel
		silt fines		SM	<15% gravel poorly-graded sand with clay
		clay fines		SC	≥15% gravel poorly-graded sand with clay and gravel

## Density of Granular Soils

Density	N-value
Very Loose	< 5
Loose	5 - 10
Medium Dense	11 - 30
Dense	31 - 50
Very Dense	> 50

## Minor Constituent Descriptors

Term	Percent Present
Trace	< 5 %
Few	5 to 10 %
Little	15 to 25 %
Some	30 to 45 %
Mostly	50 to 100 %

Note: This field guide is intended as a quick-reference guide for basic soil logging information. More detailed information is provided in ASTM D2488.

# FIELD GUIDE FOR USCS SOIL CLASSIFICATION

SEPTEMBER 1, 2020; REV 0



## Fine Grained Soil Flow Chart

Group Symbol

Group Name

LL<50 slightly to moderately sticky when wet	- medium plasticity - none to slow dilatancy - medium to high dry strength	CL	<30% sand & gravel	<15% sand & gravel		lean clay
				15-29% sand & gravel	sand ≥ gravel sand < gravel	lean clay with sand lean clay with gravel
			≥30% sand & gravel	sand ≥ gravel	<15% gravel ≥15% gravel	sandy lean clay sandy lean clay with gravel
				sand < gravel	<15% sand ≥15% sand	gravelly lean clay gravelly lean clay with sand
	- nonplastic to low plasticity - slow to rapid dilatancy - none to low dry strength	ML	<30% sand & gravel	<15% sand & gravel		silt
				15-29% sand & gravel	sand ≥ gravel sand < gravel	silt with clay silt with gravel
			≥30% sand & gravel	sand ≥ gravel	<15% gravel ≥15% gravel	sandy silt sandy silt with gravel
				sand < gravel	<15% sand ≥15% sand	gravelly silt gravelly silt with sand
LL>50 very sticky when wet	- high plasticity - no dilatancy - high to very high dry strength	CH	<30% sand & gravel	<15% sand & gravel		fat clay
				15-29% sand & gravel	sand ≥ gravel sand < gravel	fat clay with sand fat clay with gravel
			≥30% sand & gravel	sand ≥ gravel	<15% gravel ≥15% gravel	sandy fat clay sandy fat clay with gravel
				sand < gravel	<15% sand ≥15% sand	gravelly fat clay gravelly fat clay with sand
	- low to medium plasticity - none to slow dilatancy - low to medium dry strength	MH	Elastic silt soil is uncommon. If encountered, follow group name convention for other fine grained soils. (i.e. elastic silt, elastic silt with sand, elastic silt with gravel, sandy elastic silt, etc.)			

\* Record as organic soil (OL/OH) if there is enough organic particles to influence soil properties. Follow group name convention for other fine grained soils.

## Plasticity of Cohesive Soils

Nonplastic	A 1/8-in. (3-mm) thread cannot be rolled at any water content
Low	The thread can barely be rolled and the lump cannot be formed when drier than the plastic limit.
Medium	The thread is easy to roll and not much time is required to reach the plastic limit. The thread cannot be rerolled after reaching the plastic limit. The lump crumbles when drier than the plastic limit.
High	It takes considerable time rolling and kneading to reach the plastic limit. The thread can be rerolled several times after reaching the plastic limit. The lump can be formed without crumbling when drier than the plastic limit.

## Consistency of Cohesive Soils

Consistency	SPT N-value	Pocket pen (tsf)	Hand Manipulation	<i>Note:</i> <i>Order of priority in determining consistency of cohesive soils:</i> 1. Field Vane Shear Test 2. Torvane 3. Pocket Pen 4. N-value
Very Soft	<2	<0.25	Easily penetrated >1 in. by thumb	
Soft	2 – 4	0.25 - 0.5	Easily penetrated ~1 in. by thumb	
Med. Stiff	5 – 8	0.5 - 1.0	Penetrated by thumb with moderate effort	
Stiff	9 – 15	1.0 - 2.0	Readily indented by thumb but not penetrated	
Very Stiff	16 - 30	2.0 - 4.0	Readily indented but thumbnails, but thumb will not indent	
Hard	>30	>4.0	Thumbnail will not indent soil	

## Particle Size Distribution

Material	Fraction	Sieve Size	Grain Size (mm)	Approximate Scale Size
Boulders		12 in. +	300 +	Basketball
Cobbles		3 - 12 in.	300 - 75	Baseball to basket ball
Gravel	Coarse	3/4 - 3 in.	75 - 19	Thumb to baseball
	Fine	No 4 - 3/4 in.	19 - 4.75	pea to thumb
Sand	Coarse	No 10 - No 4	4.75 - 2	rock salt to pea
	Medium	No 40 - No 10	2 - 0.425	sugar to rock salt
	Fine	No 200 - No 40	0.425 - 0.075	flour to sugar
Fines		Passing No 200	< 0.075	smaller than flour

## Moisture Condition of Soils

Dry	Dusty, dry to the touch
Moist	Damp but no visible water
Wet	Visible free water



Arcadis U.S., Inc.  
One Lincoln Center, 110 West Fayette Street, Suite 300  
Syracuse  
New York 13202  
Phone: 315 446 9120  
Fax: 315 449 0017  
[www.arcadis.com](http://www.arcadis.com)